

High Capacity SSDs in the Enterprise

Scott Shadley

Sr. Technical Manager SSD Marketing STEC, Inc.



Lemory Consideration Required...

Interface Technology

Much like the movie format wars... BetaMAX? HD DVD?

Cost Requirements

Designer desires vs Price club budget

Media Restrictions


Microfiber or Leather?

The Solution

What's under the hood




EastMemory Interface Technologies Synchronous vs. A-Synchronous NAND



Fibre Channel, SAS, SATA protocols



3.5"/2.5"/1.8" Form Factors











The path to the best TCO of the SSD usage model

SLC vs. MLC media the pricing war



The Challenges with enabling MLC




What needs to be done for MLC to work


Controller technology

Advancements in ECC Write Mitigation techniques Read/Program Disturb prevention



Data Endurance Management









Just a "snapshot" of the available S.M.A.R.T attributes for use None are as complete as the STEC attribute set to date.

Attribute	Flags	Туре
Program Fail Count	0x32	Advisory
Reallocated Sector Count	0x32	Advisory
Erase/Program Cycle Count	0x32	Advisory
Wear Leveling Count	0x32	Advisory

Comprehensive Endurance monitoring

STEC monitors and tracks in all drives Erase activity counter Error conditions and events





Utilizing the proper techniques and solutions will enable MLC SSDs moving forward

MLC-Based SSDs are being qualified at key customers

Endurance mitigation is a key in providing a long life to SSDs

Controller technology must remain steps ahead of the media

